


XPEL RX PROTECTION FILM is a patented, medical grade self-adhesive, clear-coated thermoplastic polyurethane film designed to protect commercial monitors, personal devices, and other surfaces. **XPEL RX** is specifically formulated to resist the growth of microbes on its surface. Combining the medical grade strength of our Silver Ion material with its unrivaled impact resistance and HD clarity, **XPEL RX PROTECTION FILM** is the ultimate in device protection.

PRODUCT CONSTRUCTION



GENERAL CHARACTERISTICS

PROPERTIES	TYPICAL VALUES	TEST METHOD
Peel Adhesion	Average oz/in (N/m)	
Stainless Steel	49 (539)	ASTM D 903 (Modified 72 hr. RT dwell time)
Acrylic	97 (1067)	
Glass	51 (561)	
Polypropylene	11 (121)	
Polyethylene	10 (110)	
Expected Shear (hours)	50	ASTM D 3654 Method A (1 hr. dwell, 1 sq. in, 4 lb. load)
Tack (g)	500	ASTM D 2979

* For guidance only, not to be used for setting specifications. Due to the custom nature of this product, the data presented are based on three or less production runs.

EXPECTED EXTERIOR LIFE	2-Year
SERVICE TEMPERATURE RANGE	-40°F to 212°F (-40°C to 100°C)
MINIMUM APPLICATION TEMPERATURE	50°F (10°C)
STORAGE STABILITY	2-Years stored at 70°F (21°C) and 50% RH